

Superline

Super-12® with an HMPE Cover

The combination of UHMwPE core and custom cover offers the unique ability to build a rope to suit a specific application.



FEATURES

- Extreme strength-to-weight ratio
- 15 x stronger than steel
- Safer than wire (low recoil)
- Hydrophobic fibre (no water absorption)
- Floats
- Low creep
- Easy to splice
- Resistant to kinking
- Maintains high strength around tight-radius bends
- Exceptional UV and chemical resistance

Superline total fibre density exceeds the ISO 10325 minimum linear density specifications for HMPE fibre rope, 12-Strand construction specifications for all diameters.

TECHNICAL

- Core: Super-12® UHMwPE
- Cover: Custom
- Construction: Double Braid

OPTIONS

- Spliced eyes
- Thimbles
- Made to length
- Blended materials
- Custom cover thickness
- Custom colours available in Stealth Fibre®, Polyester, Nylon, Polysteel®, Polyethylene & MFPP

Diameter (mm)	Core Diameter (mm)	Spliced Break Load (t)	Linear Break Load (t)
24	20	34	38
26	22	40.5	45
28	24	47	52
32	26	54	60
34	28	61.5	68.5
36	30	70	77.5
38	32	78	86.5
40	34	87	95.5
44	36	95.5	107